MOBILE SOLVENT & SUPPLY, INC.
P. O. BOX 13385
Mobile, Alabama 36663
(251) 675-9702 ♦ (800) 426-1844

TECHNICAL BULLETIN

HOT TANK COMPOUND

DEGREASER, DERUSTER, AND PAINT REMOVER

DESCRIPTION

HOT TANK COMPOUND is a heavy duty liquid alkaline product designed to be used to clean ferrous metals by the hot vat soaking method. It removes rust, grease, oils, engine varnish, grime, heat-hardened resins, tar, and other stubborn soils. It cleans automobile radiators quickly and thoroughly. Mechanical agitation may be used if desired. Agitation reduces immersion time by producing a scrubbing effect on the parts being cleaned.

DIRECTIONS

HOT TANK COMPOUND should be used at 10 - 15 percent concentration and heated to 200° F. or higher. Immersion times may vary from a few minutes to about two hours depending on concentration, temperature, and agitation. A pressure rinse with water is used to flush away the loosened soils.

When charging the tank, fill half full with cold water. Add HOT TANK COMPOUND slowly with mixing. Heat will be generated when the compound is added to the water. Add remainder of water and heat the tank.

CAUTION

Corrosive, contains sodium hydroxide, UN 1824. Corrosive to animal tissues. Eye contact may cause severe burns or blindness. In case of eye contact, immediately flush with water for at least 15 minutes and get medical aid. Skin contact may cause severe irritation or chemical burns. In case of skin contact, flush with water. Ingestion may cause severe irritation or damage to the mucous membranes of the mouth, throat, and digestive tract. If swallowed, DO NOT INDUCE VOMITING, immediately drink large amounts of water and get medical aid.

NOTICE

Mobile Solvent & Supply, Inc. products are safe and effective when used as directed. When using as a cleaner, always test a small area for adverse reaction. Since the manufacturer cannot control conditions or method of application, no warranty or liability beyond replacement of defective product is offered.

◆ KEEP OUT OF REACH OF CHILDREN ◆